

2-Strang-GrabiQ-Kettengehänge, mit Ovalring und Multikupplung

GrabiQ Kettengehänge

Artikel Name kurz	Ketten- Durchmesser	Öse	Abmessung L min [m]	Verkürzer	Kette Komponente	Haken- Komponente	WLL t Winkel 0° - 45° [t]
2leg Chain Assembly GrabiQ MF CG EGKN 8 3500	8 mm	GrabiQ ML w Flat Access 4t	-	GrabiQ ConnLink- Shortener 2.5t 8mm	KLA-8-10 G10 2.5t	GrabiQ Clevis Sling Hook 2.5t 8mm	3.5
2leg Chain Assembly GrabiQ MF CG EGKN 10 5600	10 mm	GrabiQ ML w Flat Access 7.5t	-	GrabiQ ConnLink- Shortener 4t 10mm	KLA-10-10 G10 4t	GrabiQ Clevis Sling Hook 4t 10mm	5.6
2leg Chain Assembly GrabiQ MF CG GBK 8 3500	8 mm	GrabiQ ML w Flat Access 4t	0.5	GrabiQ ConnLink- Shortener 2.5t 8mm	KLA-8-10 G10 2.5t	GrabiQ Clevis Safety Hook 2.5t 8mm	3.5
2leg Chain Assembly GrabiQ MF CG GBK 10 5600	10 mm	GrabiQ ML w Flat Access 7.5t	0.6	GrabiQ ConnLink- Shortener 4t 10mm	KLA-10-10 G10 4t	GrabiQ Clevis Safety Hook 4t 10mm	5.6

Artikel Name kurz	WLL t Winkel 45° - 60° [t]	WLL kg Winkel 0° - 45° [kg]	WLL kg Winkel 45° - 60° [kg]	Gewicht für 1m [kg]	Gewicht pro Meter [kg/m]
2leg Chain Assembly GrabiQ MF CG EGKN 8 3500	2.5	3500	2500	3.7	2.8
2leg Chain Assembly GrabiQ MF CG EGKN 10 5600	4	5600	4000	6.3	4.6
2leg Chain Assembly GrabiQ MF CG GBK 8 3500	2.5	3500	2500	4.2	2.8
2leg Chain Assembly GrabiQ MF CG GBK 10 5600	4	5600	4000	7.1	4.6





BESTELLNUMMERN

WLL t Winkel 0°- 45°	Haken-Komponente	8 mm	10 mm
3.5 t	 GrabiQ Clevis Safety Hook 2.5t 8mm	2017334	-
3.5 t	 GrabiQ Clevis Sling Hook 2.5t 8mm	2017336	-
5.6 t	 GrabiQ Clevis Safety Hook 4t 10mm	-	2017335
5.6 t	 GrabiQ Clevis Sling Hook 4t 10mm	-	2017337

■ Klasse	100
■ Hauptmaterial	Stahl
■ Temperaturbereich	-40° C to + 200° C
■ Verpackungseinheit (VPE) Inhalt	1

