



Magnum-X

Die neue Dimension in der Hebetchnik

Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	ca. Auflagebreite unter Last in mm [mm]	ca. Auflagedicke unter Last in mm [mm]	Nettogewicht kg [kg]
Magnum-X 5t 2m	5000	5	2	1.0	36	6	0.94
Magnum-X 5t 3m	5000	5	3	1.0	36	6	1.41
Magnum-X 5t 4m	5000	5	4	1.0	36	6	1.88
Magnum-X 5t 5m	5000	5	5	1.0	36	6	2.35
Magnum-X 5t 6m	5000	5	6	1.0	36	6	2.82
Magnum-X 5t 7m	5000	5	7	1.0	36	6	3.29
Magnum-X 5t 8m	5000	5	8	1.0	36	6	3.76
Magnum-X 10t 4m	10000	10	4	2	67	11	4.1
Magnum-X 10t 5m	10000	10	5	2	67	11	5
Magnum-X 10t 6m	10000	10	6	2	67	11	5.9
Magnum-X 10t 7m	10000	10	7	2	67	11	6.8
Magnum-X 10t 8m	10000	10	8	2	67	11	7.7
Magnum-X 10t 10m	10000	10	10	2	67	11	9.5
Magnum-X 10t 12m	10000	10	12	2	67	11	10.8
Magnum-X 20t 4m	20000	20	4	2	88	13	7.7
Magnum-X 20t 5m	20000	20	5	2	88	13	9.5
Magnum-X 20t 6m	20000	20	6	2	88	13	11.3
Magnum-X 20t 7m	20000	20	7	2	88	13	13.1
Magnum-X 20t 8m	20000	20	8	2	88	13	14.9
Magnum-X 20t 10m	20000	20	10	2	88	13	18.5



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	ca. Auflagebreite unter Last in mm [mm]	ca. Auflagedicke unter Last in mm [mm]	Nettogewicht kg [kg]
Magnum-X 20t 12m	20000	20	12	2	88	13	21.6
Magnum-X 30t 4m	30000	30	4	2	91	23	12.1
Magnum-X 30t 5m	30000	30	5	2	91	23	15
Magnum-X 30t 6m	30000	30	6	2	91	23	17.9
Magnum-X 30t 7m	30000	30	7	2	91	23	20.8
Magnum-X 30t 8m	30000	30	8	2	91	23	23.7
Magnum-X 30t 10m	30000	30	10	2	91	23	29.5
Magnum-X 30t 12m	30000	30	12	2	91	23	27.6
Magnum-X 40t 4m	40000	40	4	2	101	25	16.1
Magnum-X 40t 5m	40000	40	5	2	101	25	20
Magnum-X 40t 6m	40000	40	6	2	101	25	23.9
Magnum-X 40t 7m	40000	40	7	2	101	25	27.8
Magnum-X 40t 8m	40000	40	8	2	101	25	31.7
Magnum-X 40t 10m	40000	40	10	2	101	25	39.5
Magnum-X 40t 12m	40000	40	12	2	101	25	42
Magnum-X 50t 4m	50000	50	4	2	143	24	21.3
Magnum-X 50t 5m	50000	50	5	2	143	24	26.5
Magnum-X 50t 6m	50000	50	6	2	143	24	31.7
Magnum-X 50t 7m	50000	50	7	2	143	24	36.9
Magnum-X 50t 8m	50000	50	8	2	143	24	42.1
Magnum-X 50t 10m	50000	50	10	2	143	24	52.5



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	ca. Auflagebreite unter Last in mm [mm]	ca. Aufledgedicke unter Last in mm [mm]	Nettogewicht kg [kg]
Magnum-X 50t 12m	50000	50	12	2	143	24	62.4
Magnum-X 60t 4m	60000	60	4	3	142	26	28.9
Magnum-X 60t 5m	60000	60	5	3	142	26	36
Magnum-X 60t 6m	60000	60	6	3	142	26	43.1
Magnum-X 60t 7m	60000	60	7	3	142	26	50.2
Magnum-X 60t 8m	60000	60	8	3	142	26	57.3
Magnum-X 60t 10m	60000	60	10	3	142	26	71.5
Magnum-X 60t 12m	60000	60	12	3	142	26	69.6

Artikel Name kurz	Gewicht pro Meter [kg/m]	Farbe
Magnum-X 5t 2m	0.47	Rot
Magnum-X 5t 3m	0.47	Rot
Magnum-X 5t 4m	0.47	Rot
Magnum-X 5t 5m	0.47	Rot
Magnum-X 5t 6m	0.47	Rot
Magnum-X 5t 7m	0.47	Rot
Magnum-X 5t 8m	0.47	Rot
Magnum-X 10t 4m	0.9	Orange
Magnum-X 10t 5m	0.9	Orange
Magnum-X 10t 6m	0.9	Orange
Magnum-X 10t 7m	0.9	Orange
Magnum-X 10t 8m	0.9	Orange
Magnum-X 10t 10m	0.9	Orange
Magnum-X 10t 12m	0.9	Orange



Artikel Name kurz	Gewicht pro Meter [kg/m]	Farbe
Magnum-X 20t 4m	1.8	Orange
Magnum-X 20t 5m	1.8	Orange
Magnum-X 20t 6m	1.8	Orange
Magnum-X 20t 7m	1.8	Orange
Magnum-X 20t 8m	1.8	Orange
Magnum-X 20t 10m	1.8	Orange
Magnum-X 20t 12m	1.8	Orange
Magnum-X 30t 4m	3.27	Orange
Magnum-X 30t 5m	3.27	Orange
Magnum-X 30t 6m	3.27	Orange
Magnum-X 30t 7m	3.27	Orange
Magnum-X 30t 8m	3.27	Orange
Magnum-X 30t 10m	3.27	Orange
Magnum-X 30t 12m	3.27	Orange
Magnum-X 40t 4m	3.5	Orange
Magnum-X 40t 5m	3.5	Orange
Magnum-X 40t 6m	3.5	Orange
Magnum-X 40t 7m	3.5	Orange
Magnum-X 40t 8m	3.5	Orange
Magnum-X 40t 10m	3.5	Orange
Magnum-X 40t 12m	3.5	Orange
Magnum-X 50t 4m	5.2	Orange
Magnum-X 50t 5m	5.2	Orange
Magnum-X 50t 6m	5.2	Orange
Magnum-X 50t 7m	5.2	Orange
Magnum-X 50t 8m	5.2	Orange
Magnum-X 50t 10m	5.2	Orange



Artikel Name kurz	Gewicht pro Meter [kg/m]	Farbe
Magnum-X 50t 12m	5.2	Orange
Magnum-X 60t 4m	5.8	Orange
Magnum-X 60t 5m	5.8	Orange
Magnum-X 60t 6m	5.8	Orange
Magnum-X 60t 7m	5.8	Orange
Magnum-X 60t 8m	5.8	Orange
Magnum-X 60t 10m	5.8	Orange
Magnum-X 60t 12m	5.8	Orange

BESTELLNUMMERN

Länge L1	5000 kg	10000 kg	20000 kg	30000 kg	40000 kg	50000 kg	60000 kg
2 m	2025045	-	-	-	-	-	-
3 m	2026602	-	-	-	-	-	-
4 m	2010959	2002763	2002765	2002769	2002771	2002773	2002775
5 m	2010960	2002764	2002766	2002770	2002772	2002774	2002776
6 m	2010961	2003251	2003253	2003257	2003259	2003261	2003263
7 m	2010962	2003252	2003254	2003258	2003260	2003262	2003264
8 m	2010963	2003738	2003739	2003741	2003742	2003743	2003744
10 m	-	2014760	2014762	2014765	2014767	2014769	2014771
12 m	-	2014761	2014763	2014766	2014768	2014770	2014772

■ Normen	EN 1492-2: 2000
■ Hauptmaterial	Hochleistungspolyester
■ Temperaturbereich	- 40 tot + 100°C
■ Etikettenschutz	Ja
■ Verpackungseinheit (VPE) Inhalt	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

