



Magnum-X SHORT

La "version courte"

Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	Surface de contact sous charge [mm]	Épaisseur de contact sous charge [mm]	Poids net [kg]
Magnum-X short 10000 0.5m	10000	10	0.5	55	10	-
Magnum-X short 10000 1m	10000	10	1	55	10	-
Magnum-X short 10000 1.5m	10000	10	1.5	55	10	-
Magnum-X short 10000 2m	10000	10	2	55	10	-
Magnum-X short 10000 2.5m	10000	10	2.5	55	10	-
Magnum-X short 10000 3m	10000	10	3	55	10	3.3
Magnum-X short 20000 0.5m	20000	20	0.5	70	13	-
Magnum-X short 20000 1m	20000	20	1	70	13	-
Magnum-X short 20000 1.5m	20000	20	1.5	70	13	-
Magnum-X short 20000 2m	20000	20	2	70	13	-
Magnum-X short 20000 2.5m	20000	20	2.5	70	13	-
Magnum-X short 20000 3m	20000	20	3	70	13	7.8
Magnum-X short 30000 1m	30000	30	1	100	21	-
Magnum-X short 30000 1.5m	30000	30	1.5	100	21	-
Magnum-X short 30000 2m	30000	30	2	100	21	-
Magnum-X short 30000 2.5m	30000	30	2.5	100	21	-
Magnum-X short 30000 3m	30000	30	3	100	21	11.4



NUMÉROS DE COMMANDE

Dimension L1	10000 kg	20000 kg	30000 kg
0.5 m	2015301	2015331	-
1 m	2002791	2002793	2002795
1.5 m	2002792	2002794	2002796
2 m	2003279	2003280	2003281
2.5 m	2015304	2015333	2015336
3 m	2015305	2015334	2015337

■ Matériel principal	Polyester haute performance
■ Couleur	Orange
■ Plage de température	- 40 tot + 100°C
■ Qualité	Professional
■ Protection d'étiquette	Oui
■ Contenu des unités d'emballage (UE)	1

