



MagnumPlus

Zuverlässige Unterstützung, starker Halt, optimales Handling und hohe Verschleißfestigkeit Rundschlinge für schwere Lasten

Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	ca. Auflagebreite unter Last in mm [mm]	ca. Aufledgedicke unter Last in mm [mm]	Nettogewicht kg [kg]
MagnumPlus 10t 2m	10000	10	2	1	93	12	4.4
MagnumPlus 10t 2.5m	10000	10	2.5	1	93	12	5.5
MagnumPlus 10t 3m	10000	10	3	1	93	12	6.6
MagnumPlus 10t 4m	10000	10	4	1	93	12	9.3
MagnumPlus 10t 5m	10000	10	5	1	93	12	11.5
MagnumPlus 10t 6m	10000	10	6	1	93	12	13.7
MagnumPlus 10t 7m	10000	10	7	1	93	12	15.9
MagnumPlus 10t 8m	10000	10	8	1	93	12	18.1
MagnumPlus 15t 2m	15000	15	2	1	110	15	5.4
MagnumPlus 15t 2.5m	15000	15	2.5	1	110	15	6.75
MagnumPlus 15t 3m	15000	15	3	1	110	15	8.1
MagnumPlus 15t 4m	15000	15	4	1	110	15	13.3
MagnumPlus 15t 5m	15000	15	5	1	110	15	16.5
MagnumPlus 15t 6m	15000	15	6	1	110	15	19.7
MagnumPlus 15t 7.0m	15000	15	7	1	110	15	22.9
MagnumPlus 15t 8m	15000	15	8	1	110	15	26.1
MagnumPlus 20t 2m	20000	20	2	1.3	140	18	8
MagnumPlus 20t 2.5m	20000	20	2.5	1.3	140	18	10
MagnumPlus 20t 3m	20000	20	3	1.3	140	18	12



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	ca. Auflagebreite unter Last in mm [mm]	ca. Aufledgedicke unter Last in mm [mm]	Nettogewicht kg [kg]
MagnumPlus 20t 4m	20000	20	4	1.3	140	18	18.1
MagnumPlus 20t 5m	20000	20	5	1.3	140	18	22.5
MagnumPlus 20t 6m	20000	20	6	1.3	140	18	26.9
MagnumPlus 20t 7m	20000	20	7	1.3	140	18	31.3
MagnumPlus 25t 2.5m	25000	25	2.5	1.3	153	25	12.5
MagnumPlus 25t 3m	25000	25	3	1.3	153	25	15
MagnumPlus 25t 4m	25000	25	4	1.3	153	25	22.9
MagnumPlus 25t 5m	25000	25	5	1.3	153	25	28.5
MagnumPlus 25t 6m	25000	25	6	1.3	153	25	34.1
MagnumPlus 25t 7m	25000	25	7	1.3	153	25	39.7
MagnumPlus 25t 8m	25000	25	8	1.3	153	25	45.3
MagnumPlus 30t 3m	30000	30	3	1.3	165	19	19.5
MagnumPlus 30t 4m	30000	30	4	1.3	165	19	30.1
MagnumPlus 30t 5m	30000	30	5	1.3	165	19	37.5
MagnumPlus 30t 6m	30000	30	6	1.3	165	19	44.9
MagnumPlus 30t 7m	30000	30	7	1.3	165	19	52.3
MagnumPlus 30t 8m	30000	30	8	1.3	165	19	59.7
MagnumPlus 40t 3m	40000	40	3	3	180	22	29.1
MagnumPlus 40t 4m	40000	40	4	3	180	22	40.5
MagnumPlus 40t 5m	40000	40	5	3	180	22	50.5
MagnumPlus 40t 6m	40000	40	6	3	180	22	60.5



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	ca. Auflagebreite unter Last in mm [mm]	ca. Auflagedicke unter Last in mm [mm]	Nettogewicht kg [kg]
MagnumPlus 40t 7m	40000	40	7	3	180	22	70.5
MagnumPlus 40t 8m	40000	40	8	3	180	22	80.5
MagnumPlus 50t 3m	50000	50	3	3	208	24	37.5
MagnumPlus 50t 4m	50000	50	4	3	208	24	52.5
MagnumPlus 50t 5m	50000	50	5	3	208	24	65.5
MagnumPlus 50t 6m	50000	50	6	3	208	24	78.5
MagnumPlus 50t 7m	50000	50	7	3	208	24	91.5
MagnumPlus 50t 8m	50000	50	8	3	208	24	104.5
MagnumPlus 60t 3m	60000	60	3	3	244	27	49.8
MagnumPlus 60t 4m	60000	60	4	3	244	27	59.7
MagnumPlus 60t 5m	60000	60	5	3	244	27	74.5
MagnumPlus 60t 6m	60000	60	6	3	244	27	89.3
MagnumPlus 60t 7m	60000	60	7	3	244	27	104.1
MagnumPlus 60t 8m	60000	60	8	3	244	27	118.9

Artikel Name kurz	Gewicht pro Meter [kg/m]
MagnumPlus 10t 2m	2.2
MagnumPlus 10t 2.5m	2.2
MagnumPlus 10t 3m	2.2
MagnumPlus 10t 4m	2.2
MagnumPlus 10t 5m	2.2
MagnumPlus 10t 6m	2.2
MagnumPlus 10t 7m	2.2
MagnumPlus 10t 8m	2.2



Artikel Name kurz	Gewicht pro Meter [kg/m]
MagnumPlus 15t 2m	2.7
MagnumPlus 15t 2.5m	2.7
MagnumPlus 15t 3m	2.7
MagnumPlus 15t 4m	2.7
MagnumPlus 15t 5m	2.7
MagnumPlus 15t 6m	2.7
MagnumPlus 15t 7.0m	2.7
MagnumPlus 15t 8m	2.7
MagnumPlus 20t 2m	4
MagnumPlus 20t 2.5m	4
MagnumPlus 20t 3m	4
MagnumPlus 20t 4m	4
MagnumPlus 20t 5m	4
MagnumPlus 20t 6m	4
MagnumPlus 20t 7m	4
MagnumPlus 25t 2.5m	5
MagnumPlus 25t 3m	5
MagnumPlus 25t 4m	5
MagnumPlus 25t 5m	5
MagnumPlus 25t 6m	5
MagnumPlus 25t 7m	5
MagnumPlus 25t 8m	5
MagnumPlus 30t 3m	6.5
MagnumPlus 30t 4m	6.5
MagnumPlus 30t 5m	6.5
MagnumPlus 30t 6m	6.5
MagnumPlus 30t 7m	6.5
MagnumPlus 30t 8m	6.5
MagnumPlus 40t 3m	9.7
MagnumPlus 40t 4m	9.7
MagnumPlus 40t 5m	9.7
MagnumPlus 40t 6m	9.7
MagnumPlus 40t 7m	9.7



Artikel Name kurz	Gewicht pro Meter [kg/m]
MagnumPlus 40t 8m	9.7
MagnumPlus 50t 3m	12.5
MagnumPlus 50t 4m	12.5
MagnumPlus 50t 5m	12.5
MagnumPlus 50t 6m	12.5
MagnumPlus 50t 7m	12.5
MagnumPlus 50t 8m	12.5
MagnumPlus 60t 3m	16.6
MagnumPlus 60t 4m	16.6
MagnumPlus 60t 5m	16.6
MagnumPlus 60t 6m	16.6
MagnumPlus 60t 7m	16.6
MagnumPlus 60t 8m	16.6

BESTELLNUMMERN

Länge L1	10000 kg	15000 kg	20000 kg	25000 kg	30000 kg	40000 kg	50000 kg	60000 kg
2 m	2020851	2027560	2023220	-	-	-	-	-
2.5 m	2020997	2020999	2021001	2021003	-	-	-	-
3 m	2020998	2021000	2021002	2021004	2021006	2021008	2026463	2026497
4 m	2002743	2002745	2002747	2002749	2002751	2002753	2002755	2002757
5 m	2002744	2002746	2002748	2002750	2002752	2002754	2002756	2002758
6 m	2003231	2003233	2003235	2003237	2003239	2003241	2003243	2003245
7 m	2003232	2003234	2003236	2003238	2003240	2003242	2003244	2003246
8 m	2003728	2003729	-	2003731	2003732	2003733	2003734	2003735

■ Normen	EN 1492-2: 2000
■ Hauptmaterial	Polyester
■ Farbe	Orange
■ Temperaturbereich	- 40 tot + 100°C
■ Etikettenschutz	Ja
■ Verpackungseinheit (VPE) Inhalt	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - Nutzlänge.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

