



PowerFlex








Zweifach geschütztes Hebeband für raue Arbeitsbedingungen

Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Gurtband Breite B [mm]	Nettogewicht kg [kg]	Farbe
PB 1000-P2 2m	1000	1	2	1	30	0.7	violett
PB 1000-P2 3m	1000	1	3	1	30	1	violett
PB 1000-P2 4m	1000	1	4	1	30	1.3	violett
PB 1000-P2 5m	1000	1	5	1	30	1.6	violett
PB 1000-P2 6m	1000	1	6	1	30	1.9	violett
PB 2000-P2 2m	2000	2	2	1	60	1.6	Grün
PB 2000-P2 2.5m	2000	2	2.5	1	60	1.9	Grün
PB 2000-P2 3m	2000	2	3	1	60	2.2	Grün
PB 2000-P2 4m	2000	2	4	1	60	2.8	Grün
PB 2000-P2 5m	2000	2	5	1	60	3.4	Grün
PB 2000-P2 6m	2000	2	6	1	60	4	Grün
PB 2000-P2 7m	2000	2	7	1	60	4.5	Grün
PB 3000-P2 2m	3000	3	2	1.3	90	2.1	Gelb
PB 3000-P2 3m	3000	3	3	1.3	90	2.9	Gelb
PB 3000-P2 4m	3000	3	4	1.3	90	3.7	Gelb
PB 3000-P2 5m	3000	3	5	1.3	90	4.5	Gelb
PB 3000-P2 6m	3000	3	6	1.3	90	5.3	Gelb
PB 4000-P2 2m	4000	4	2	1.3	120	2.9	Grau
PB 4000-P2 3m	4000	4	3	1.3	120	4	Grau
PB 4000-P2 4m	4000	4	4	1.3	120	5.1	Grau
PB 4000-P2 5m	4000	4	5	1.3	120	6.2	Grau
PB 4000-P2 6m	4000	4	6	1.3	120	7.3	Grau
PB 5000-P2 2m	5000	5	2	1.5	150	3.8	Rot
PB 5000-P2 3m	5000	5	3	1.5	150	5.2	Rot
PB 5000-P2 4m	5000	5	4	1.5	150	6.6	Rot
PB 5000-P2 5m	5000	5	5	1.5	150	8	Rot



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Gurtband Breite B [mm]	Nettogewicht kg [kg]	Farbe
PB 5000-P2 6m	5000	5	6	1.5	150	9.4	Rot

BESTELLNUMMERN

Länge L1	End Komponente	1000 kg	2000 kg	3000 kg	4000 kg	5000 kg
2 m	 -	2015456	2015462	2015469	2015474	2015479
2.5 m	 -	-	2015463	-	-	-
3 m	 -	2015457	2015464	2015470	2015475	2015480
4 m	 -	2015458	2015465	2015471	2015476	2015481
5 m	 -	2015459	2015466	2015472	2015477	2015482
6 m	 -	2015460	2015467	2015473	2015478	2015483
7 m	 -	-	2015468	-	-	-

■ Normen	EN 1492-1: 2000
■ Hauptmaterial	Polyester
■ Temperaturbereich	-40°C / +100°C
■ Etikettenschutz	Ja
■ Verpackungseinheit (VPE) Inhalt	1

