



PowerFlex

Sangle de levage avec protection anti-abrasion fusionnée avec 2 couches portantes

Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Largeur de la sangle B [mm]	Poids net [kg]	Couleur
PB 1000-P2 2m	1000	1	2	1	30	0.7	Violet
PB 1000-P2 3m	1000	1	3	1	30	1	Violet
PB 1000-P2 4m	1000	1	4	1	30	1.3	Violet
PB 1000-P2 5m	1000	1	5	1	30	1.6	Violet
PB 1000-P2 6m	1000	1	6	1	30	1.9	Violet
PB 2000-P2 2m	2000	2	2	1	60	1.6	Vert
PB 2000-P2 2.5m	2000	2	2.5	1	60	1.9	Vert
PB 2000-P2 3m	2000	2	3	1	60	2.2	Vert
PB 2000-P2 4m	2000	2	4	1	60	2.8	Vert
PB 2000-P2 5m	2000	2	5	1	60	3.4	Vert
PB 2000-P2 6m	2000	2	6	1	60	4	Vert
PB 2000-P2 7m	2000	2	7	1	60	4.5	Vert
PB 3000-P2 2m	3000	3	2	1.3	90	2.1	Jaune
PB 3000-P2 3m	3000	3	3	1.3	90	2.9	Jaune
PB 3000-P2 4m	3000	3	4	1.3	90	3.7	Jaune
PB 3000-P2 5m	3000	3	5	1.3	90	4.5	Jaune
PB 3000-P2 6m	3000	3	6	1.3	90	5.3	Jaune
PB 4000-P2 2m	4000	4	2	1.3	120	2.9	Gris
PB 4000-P2 3m	4000	4	3	1.3	120	4	Gris
PB 4000-P2 4m	4000	4	4	1.3	120	5.1	Gris
PB 4000-P2 5m	4000	4	5	1.3	120	6.2	Gris
PB 4000-P2 6m	4000	4	6	1.3	120	7.3	Gris
PB 5000-P2 2m	5000	5	2	1.5	150	3.8	Rouge
PB 5000-P2 3m	5000	5	3	1.5	150	5.2	Rouge
PB 5000-P2 4m	5000	5	4	1.5	150	6.6	Rouge
PB 5000-P2 5m	5000	5	5	1.5	150	8	Rouge



Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Largeur de la sangle B [mm]	Poids net [kg]	Couleur
PB 5000-P2 6m	5000	5	6	1.5	150	9.4	Rouge

NUMÉROS DE COMMANDE

Dimension L1	Composant de l'élément d'extrémité	1000 kg	2000 kg	3000 kg	4000 kg	5000 kg
2 m	-	2015456	2015462	2015469	2015474	2015479
2.5 m	-	-	2015463	-	-	-
3 m	-	2015457	2015464	2015470	2015475	2015480
4 m	-	2015458	2015465	2015471	2015476	2015481
5 m	-	2015459	2015466	2015472	2015477	2015482
6 m	-	2015460	2015467	2015473	2015478	2015483
7 m	-	-	2015468	-	-	-

■ Normes	EN 1492-1: 2000
■ Matériel principal	Polyester
■ Plage de température	-40°C / +100°C
■ Protection d'étiquette	Oui
■ Contenu des unités d'emballage (UE)	1

