



## PowerStar 2-lagig, konfigurierbar

| Artikel Name kurz      | WLL<br>[kg] | WLL<br>[t] | Gewicht für 1m<br>[kg] | Gewicht pro Meter<br>[kg/m] |
|------------------------|-------------|------------|------------------------|-----------------------------|
| PowerStar 2ply 500 CL  | 500         | 0.5        | 0.3                    | 0.2                         |
| PowerStar 2ply 1000 CL | 1000        | 1          | 0.3                    | 0.2                         |
| PowerStar 2ply 2000 CL | 2000        | 2          | -                      | -                           |
| PowerStar 2ply 3000 CL | 3000        | 3          | 1                      | 0.6                         |
| PowerStar 2ply 4000 CL | 4000        | 4          | 1.4                    | 0.8                         |
| PowerStar 2ply 5000 CL | 5000        | 5          | 1.7                    | 10                          |
| PowerStar 2ply 6000 CL | 6000        | 6          | 2.2                    | 12                          |

## BESTELLNUMMERN

Error: Order table could not be generated.; Please check your preset and products.

|                                   |                    |
|-----------------------------------|--------------------|
| ■ Normen                          | EN 1492-1: 2000    |
| ■ Hauptmaterial                   | Polyester          |
| ■ Temperaturbereich               | -40° C to + 100° C |
| ■ Qualität                        | Professional       |
| ■ Etikettenschutz                 | Ja                 |
| ■ Verpackungseinheit (VPE) Inhalt | 1                  |

