



SecuFlex

Haute résistance à la coupure sur une face et protection contre l'abrasion sur l'autre face

Nom court de l'article	WLL [kg]	L1 [m]	L1 min. [m]	Largeur de la sangle B [mm]	Épaisseur de sangle [mm]
secuflex 1000 2m	1000	2	1	30	13
secuflex 1000 3m	1000	3	1	30	13
secuflex 1000 4m	1000	4	1	30	13
secuflex 1000 5m	1000	5	1	30	13
secuflex 1000 6m	1000	6	1	30	13
secuflex 2000 2m	2000	2	1	60	13
secuflex 2000 3m	2000	3	1	60	13
secuflex 2000 4m	2000	4	1	60	13
secuflex 2000 5m	2000	5	1	60	13
secuflex 2000 6m	2000	6	1	60	13
secuflex 2000 8m	2000	8	1	60	13
secuflex 3000 2m	3000	2	1.3	90	13
secuflex 3000 3m	3000	3	1.3	90	13
secuflex 3000 4m	3000	4	1.3	90	13
secuflex 3000 5m	3000	5	1.3	90	13
secuflex 3000 6m	3000	6	1.3	90	13
secuflex 4000 2m	4000	2	1.3	120	-
secuflex 4000 3m	4000	3	1.3	120	-
secuflex 4000 4m	4000	4	1.3	120	-
secuflex 4000 5m	4000	5	1.3	120	-
secuflex 4000 6m	4000	6	1.3	120	-
secuflex 5000 2m	5000	2	1.5	150	-
secuflex 5000 3m	5000	3	1.5	150	-
secuflex 5000 4m	5000	4	1.5	150	-
secuflex 5000 5m	5000	5	1.5	150	-
secuflex 5000 6m	5000	6	1.5	150	-
secuflex 6000 2m	6000	2	1.9	180	13
secuflex 6000 3m	6000	3	1.9	180	13
secuflex 6000 4m	6000	4	1.9	180	13
secuflex 6000 5m	6000	5	1.9	180	13
secuflex 6000 6m	6000	6	1.9	180	13



NUMÉROS DE COMMANDE

WLL	2 m	3 m	4 m	5 m	6 m	8 m
1000 kg	2025156	2025157	2025158	2025159	2025160	-
2000 kg	2025162	2025163	2025164	2025165	2025166	2025167
3000 kg	2025168	2025169	2025170	2025171	2025172	-
4000 kg	2025174	2025175	2025176	2025177	2025178	-
5000 kg	2025180	2025181	2025182	2025183	2025184	-
6000 kg	2025186	2025187	2025188	2025189	2025190	-

■ Normes	EN 1492-1: 2000
■ Matériel principal	Polyester
■ Plage de température	-40°C / +100°C
■ Protection d'étiquette	Oui
■ Contenu des unités d'emballage (UE)	1

