

Levage SupraPlus EN 1492-2: 2000

02





SupraPlus Extrêmement robuste et compact

Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Surface de contact sous charge [mm]	Épaisseur de contact sous charge [mm]	Poids net [kg]
SupraPlus-X 0.5t 0.5m	500	0.5	0.5	0.5	38	4	0.1
SupraPlus-X 0.5t 0.75m	500	0.5	0.75	0.5	38	4	0.15
SupraPlus-X 0.5t 1.0m	500	0.5	1	0.5	38	4	0.2
SupraPlus-X 0.5t 1.5m	500	0.5	1.5	0.5	38	4	0.3
SupraPlus-X 0.5t 2.0m	500	0.5	2	0.5	38	4	0.4
SupraPlus-X 0.5t 2.5m	500	0.5	2.5	0.5	38	4	0.4
SupraPlus-X 0.5t 3.0m	500	0.5	3	0.5	38	4	0.4
SupraPlus-X 0.5t 5.0m	500	0.5	5	0.5	38	4	0.4
SupraPlus-X 1t 0.5m	1000	1	0.5	0.5	39	4	0.15
SupraPlus-X 1t 0.75m	1000	1	0.75	0.5	39	4	0.22
SupraPlus-X 1t 1.0m	1000	1	1	0.5	39	4	0.3
SupraPlus-X 1t 1.5m	1000	1	1.5	0.5	39	4	0.45
SupraPlus-X 1t 2.0m	1000	1	2	0.5	39	4	0.6
SupraPlus-X 1t 2.5m	1000	1	2.5	0.5	39	4	0.75
SupraPlus-X 1t 3.0m	1000	1	3	0.5	39	4	0.9
SupraPlus-X 1t 4.0m	1000	1	4	0.5	39	4	1.2
SupraPlus-X 1t 5.0m	1000	1	5	0.5	39	4	1.5
SupraPlus-X 1t 6.0m	1000	1	6	0.5	39	4	2.4
SupraPlus-X 1t 10m	1000	1	10	0.5	39	4	4
SupraPlus-X 2t 0.5m	2000	2	0.5	0.5	40	8	0.25

SpanSet AG Eichbüelstrasse 31 8618 Oetwil am See Suisse Tel.: +41 44 929 70 70 info@spanset.ch

www.spanset.ch





Levage SupraPlus EN 1492-2: 2000

02

Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Surface de contact sous charge [mm]	Épaisseur de contact sous charge [mm]	Poids net [kg]
SupraPlus-X 2t 0.75m	2000	2	0.75	0.5	40	8	0.37
SupraPlus-X 2t 1.0m	2000	2	1	0.5	40	8	0.5
SupraPlus-X 2t 1.5m	2000	2	1.5	0.5	40	8	0.75
SupraPlus-X 2t 2.0m	2000	2	2	0.5	40	8	1
SupraPlus-X 2t 2.5m	2000	2	2.5	0.5	40	8	1.25
SupraPlus-X 2t 3.0m	2000	2	3	0.5	40	8	1.5
SupraPlus-X 2t 4.0m	2000	2	4	0.5	40	8	2
SupraPlus-X 2t 5.0m	2000	2	5	0.5	40	8	2.5
SupraPlus-X 2t 6.0m	2000	2	6	0.5	40	8	3
SupraPlus-X 3t 0.5m	3000	3	0.5	0.5	48	8	-
SupraPlus-X 3t 1.0m	3000	3	1	0.5	48	8	0.6
SupraPlus-X 3t 1.5m	3000	3	1.5	0.5	48	8	0.9
SupraPlus-X 3t 2.0m	3000	3	2	0.5	48	8	1.2
SupraPlus-X 3t 2.5m	3000	3	2.5	0.5	48	8	1.5
SupraPlus-X 3t 3.0m	3000	3	3	0.5	48	8	1.8
SupraPlus-X 3t 3.5m	3000	3	3.5	0.5	48	8	2
SupraPlus-X 3t 4.0m	3000	3	4	0.5	48	8	2.4
SupraPlus-X 3t 5.0m	3000	3	5	0.5	48	8	3.0
SupraPlus-X 3t 6.0m	3000	3	6	0.5	48	8	3.6
SupraPlus-X 4t 0.5m	4000	4	0.5	0.75	54	9	0.4
SupraPlus-X 4t 1.0m	4000	4	1	0.75	54	9	0.8

SpanSet AG Eichbüelstrasse 31 8618 Oetwil am See Suisse Tel.: +41 44 929 70 70 info@spanset.ch www.spanset.ch





Levage SupraPlus EN 1492-2: 2000

02

Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Surface de contact sous charge [mm]	Épaisseur de contact sous charge [mm]	Poids net [kg]
SupraPlus-X 4t 1.5m	4000	4	1.5	0.75	54	9	1.2
SupraPlus-X 4t 2.0m	4000	4	2	0.75	54	9	1.6
SupraPlus-X 4t 2.5m	4000	4	2.5	0.75	54	9	2
SupraPlus-X 4t 3.0m	4000	4	3	0.75	54	9	2.4
SupraPlus-X 4t 4.0m	4000	4	4	0.75	54	9	3.2
SupraPlus-X 4t 5.0m	4000	4	5	0.75	54	9	4
SupraPlus-X 4t 6.0m	4000	4	6	0.75	54	9	4.8
SupraPlus-X 4t 8.0m	4000	4	8	0.75	54	9	-
SupraPlus-X 5t 0.5m	5000	5	0.5	0.75	59	11	2
SupraPlus-X 5t 1.0m	5000	5	1	0.75	59	11	1
SupraPlus-X 5t 1.5m	5000	5	1.5	0.75	59	11	1.5
SupraPlus-X 5t 2.0m	5000	5	2	0.75	59	11	2
SupraPlus-X 5t 2.5m	5000	5	2.5	0.75	59	11	2.5
SupraPlus-X 5t 3.0m	5000	5	3	0.75	59	11	3
SupraPlus-X 5t 3.5m	5000	5	3.5	0.75	59	11	3.5
SupraPlus-X 5t 4.0m	5000	5	4	0.75	59	11	4
SupraPlus-X 5t 5.0m	5000	5	5	0.75	59	11	5
SupraPlus-X 5t 6.0m	5000	5	6	0.75	59	11	6
SupraPlus-X 6t 1.0m	6000	6	1	0.75	68	11	1.2
SupraPlus-X 6t 1.5m	6000	6	1.5	0.75	68	11	1.8
SupraPlus-X 6t 2.0m	6000	6	2	0.75	68	11	2.4

SpanSet AG Eichbüelstrasse 31 8618 Oetwil am See Suisse Tel.: +41 44 929 70 70 info@spanset.ch www.spanset.ch





Levage SupraPlus EN 1492-2: 2000

02

Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min . [m]	Surface de contact sous charge [mm]	Épaisseur de contact sous charge [mm]	Poids net [kg]	
SupraPlus-X 6t 2.5m	6000	6	2.5	0.75	68	11	3	
SupraPlus-X 6t 3.0m	6000	6	3	0.75	68	11	3.6	
SupraPlus-X 6t 4.0m	6000	6	4	0.75	68	11	4.8	
SupraPlus-X 6t 5.0m	6000	6	5	0.75	68	11	6	
SupraPlus-X 6t 6.0m	6000	6	6	0.75	68	11	7.2	
SupraPlus-X 8t 1.0m	8000	8	1	0.75	74	13	1.6	
SupraPlus-X 8t 1.5m	8000	8	1.5	0.75	74	13	2.4	
SupraPlus-X 8t 2.0m	8000	8	2	0.75	74	13	-	
SupraPlus-X 8t 2.5m	8000	8	2.5	0.75	74	13	4	
SupraPlus-X 8t 3.0m	8000	8	3	0.75	74	13	4.8	
SupraPlus-X 8t 4.0m	8000	8	4	0.75	74	13	6.4	
SupraPlus-X 8t 5.0m	8000	8	5	0.75	74	74 13		
SupraPlus-X 8t 6.0m	8000	8	6	0.75	74	13	9.6	

Nom court de l'article	Poids par mètre [kg/m]	Couleur
SupraPlus-X 0.5t 0.5m	0.2	Olive
SupraPlus-X 0.5t 0.75m	0.2	Olive
SupraPlus-X 0.5t 1.0m	0.2	Olive
SupraPlus-X 0.5t 1.5m	0.2	Olive
SupraPlus-X 0.5t 2.0m	0.2	Olive
SupraPlus-X 0.5t 2.5m	0.2	Olive
SupraPlus-X 0.5t 3.0m	0.2	Olive

SpanSet AG Eichbüelstrasse 31 8618 Oetwil am See Suisse Tel.: +41 44 929 70 70 info@spanset.ch www.spanset.ch







Levage SupraPlus EN 1492-2: 2000

02

Nom court de l'article	Poids par mètre [kg/m]	Couleur
SupraPlus-X 0.5t 5.0m	0.2	Olive
SupraPlus-X 1t 0.5m	0.3	Violet
SupraPlus-X 1t 0.75m	0.3	Violet
SupraPlus-X 1t 1.0m	0.3	Violet
SupraPlus-X 1t 1.5m	0.3	Violet
SupraPlus-X 1t 2.0m	0.3	Violet
SupraPlus-X 1t 2.5m	0.3	Violet
SupraPlus-X 1t 3.0m	0.3	Violet
SupraPlus-X 1t 4.0m	0.3	Violet
SupraPlus-X 1t 5.0m	0.3	Violet
SupraPlus-X 1t 6.0m	0.3	Violet
SupraPlus-X 1t 10m	0.3	Violet
SupraPlus-X 2t 0.5m	0.5	Vert
SupraPlus-X 2t 0.75m	0.5	Vert
SupraPlus-X 2t 1.0m	0.5	Vert
SupraPlus-X 2t 1.5m	0.5	Vert
SupraPlus-X 2t 2.0m	0.5	Vert
SupraPlus-X 2t 2.5m	0.5	Vert
SupraPlus-X 2t 3.0m	0.5	Vert
SupraPlus-X 2t 4.0m	0.5	Vert
SupraPlus-X 2t 5.0m	0.5	Vert
SupraPlus-X 2t 6.0m	0.5	Vert
SupraPlus-X 3t 0.5m	0.6	Jaune
SupraPlus-X 3t 1.0m	0.6	Jaune
SupraPlus-X 3t 1.5m	0.6	Jaune
SupraPlus-X 3t 2.0m	0.6	Jaune
SupraPlus-X 3t 2.5m	0.6	Jaune Jaune

SpanSet AG Eichbüelstrasse 31 8618 Oetwil am See Suisse

Tel.: +41 44 929 70 70 info@spanset.ch www.spanset.ch







Levage SupraPlus EN 1492-2: 2000

02

Nom court de l'article	Poids par mètre [kg/m]	Couleur
SupraPlus-X 3t 3.0m	0.6	Jaune
SupraPlus-X 3t 3.5m	0.6	Jaune
SupraPlus-X 3t 4.0m	0.6	
SupraPlus-X 3t 5.0m	0.6	Jaune
SupraPlus-X 3t 6.0m	0.6	Jaune
SupraPlus-X 4t 0.5m	0.8	Gris
SupraPlus-X 4t 1.0m	0.8	Gris
SupraPlus-X 4t 1.5m	0.8	Gris
SupraPlus-X 4t 2.0m	0.8	Gris
SupraPlus-X 4t 2.5m	0.8	Gris
SupraPlus-X 4t 3.0m	0.8	Gris
SupraPlus-X 4t 4.0m	0.8	Gris
SupraPlus-X 4t 5.0m	0.8	Gris
SupraPlus-X 4t 6.0m	0.8	Gris
SupraPlus-X 4t 8.0m	0.8	Gris
SupraPlus-X 5t 0.5m	1.0	Rouge
SupraPlus-X 5t 1.0m	1.0	Rouge
SupraPlus-X 5t 1.5m	1.0	Rouge
SupraPlus-X 5t 2.0m	1.0	Rouge
SupraPlus-X 5t 2.5m	1.0	Rouge
SupraPlus-X 5t 3.0m	1.0	Rouge
SupraPlus-X 5t 3.5m	1.0	Rouge
SupraPlus-X 5t 4.0m	1.0	Rouge
SupraPlus-X 5t 5.0m	1.0	Rouge
SupraPlus-X 5t 6.0m	1.0	Rouge
SupraPlus-X 6t 1.0m	1.2	Brun
SupraPlus-X 6t 1.5m	1.2	Brun

SpanSet AG Eichbüelstrasse 31 8618 Oetwil am See Suisse

Tel.: +41 44 929 70 70 info@spanset.ch www.spanset.ch







Levage SupraPlus EN 1492-2: 2000

02

Nom court de l'article	Poids par mètre [kg/m]	Couleur
SupraPlus-X 6t 2.0m	1.2	Brun
SupraPlus-X 6t 2.5m	1.2	Brun
SupraPlus-X 6t 3.0m	1.2	Brun
SupraPlus-X 6t 4.0m	1.2	Brun
SupraPlus-X 6t 5.0m	1.2	Brun
SupraPlus-X 6t 6.0m	1.2	Brun
SupraPlus-X 8t 1.0m	1.6	Bleu
SupraPlus-X 8t 1.5m	1.6	Bleu
SupraPlus-X 8t 2.0m	1.6	Bleu
SupraPlus-X 8t 2.5m	1.6	Bleu
SupraPlus-X 8t 3.0m	1.6	Bleu
SupraPlus-X 8t 4.0m	1.6	Bleu
SupraPlus-X 8t 5.0m	1.6	Bleu
SupraPlus-X 8t 6.0m	1.6	Bleu

NUMÉROS DE COMMANDE

Dimension L1	500 kg	1000 kg	2000 kg	3000 kg	4000 kg	5000 kg	6000 kg	8000 kg
0.5 m	2019184	2019189	2019198	2027101	2027104	2027105	-	-
0.75 m	2019185	2019190	2019199	-	-	-	-	-
1 m	2019186	2019191	2019200	2019208	2024570	2024811	2024571	2024816
1.5 m	2019187	2019192	2019201	2019209	2024669	2024812	2024814	2024817
2 m	2019188	2019193	2019202	2019210	2019216	2019222	2022135	2022140
2.5 m	2027097	2019194	2019203	2019211	2019217	2024813	2024815	2024818
3 m	2027098	2019195	2019204	2019212	2019218	2019223	2022136	2022141
3.5 m	-	-	-	2027103	-	2027106	-	-
4 m	-	2019196	2019205	2019213	2019219	2019224	2022137	2022142
5 m	2027099	2019197	2019206	2019214	2019220	2019225	2022138	2022143
6 m	-	2024660	2019207	2019215	2019221	2019226	2022139	2022144
8 m	-	-	-	-	2024668	-		-
10 m		2027100	-					-

SpanSet AG Eichbüelstrasse 31 8618 Oetwil am See Suisse

Tel.: +41 44 929 70 70 info@spanset.ch www.spanset.ch







Levage SupraPlus EN 1492-2: 2000

02

■ Normes

EN 1492-2: 2000

Matériel principal

Polyester

■ Plage de température

- 40° / +100°C

■ Protection d'étiquette

Oui

Contenu des unités d'emballage (UE)

SpanSet AG Eichbüelstrasse 31 8618 Oetwil am See Suisse Tel.: +41 44 929 70 70

info@spanset.ch www.spanset.ch

