



## XOPSR

Boulon à œil vissé, autobloquant et réutilisable.

Nom court de l'article	WLL kg Angle 0° [kg]	WLL t angle 0° [t]	WLL kg Angle 90° [kg]	WLL t angle 90° [t]	A [mm]	B [mm]	C [mm]
XOPSR-00-08N	600	0.6	300	0.3	46	11	9
XOPSR-00-10N	800	0.8	400	0.4	43.7	10	9.8
XOPSR-00-12N	1500	1.5	750	0.75	54	12.5	11.5
XOPSR-01-16N	3000	3	1500	1.5	64	14.5	15.7
XOPSR-02-20N	4600	4.6	2300	2.3	74	16	18
XOPSR-03-24N	6400	6.4	3200	3.2	89.5	20.5	22
XOPSR-04-30N	9000	9	4500	4.5	111.5	25.5	28
XOPSR-07-36N	14000	14	7000	7	137	32	30
XOPSR-09-42N	18000	18	9000	9	156	38	37
XOPSR-12-48N	24000	24	12000	12	180	43	38

Nom court de l'article	D [mm]	E [mm]	K [mm]	L [mm]	M [mm]	Poids net [kg]
XOPSR-00-08N	25	30	46	12	8	0.3
XOPSR-00-10N	25	30	46	15	10	0.3
XOPSR-00-12N	30	36.5	55.5	18	12	0.46
XOPSR-01-16N	35	42	64.5	24	16	0.9
XOPSR-02-20N	40	52.5	74.5	30	20	1.15
XOPSR-03-24N	49	61	90	36	24	2.05
XOPSR-04-30N	60	75	111	45	30	4
XOPSR-07-36N	74	96.5	135	55	36	6.7
XOPSR-09-42N	82	110	158	65	42	9.5
XOPSR-12-48N	95	124.5	180	72	48	13.4



## NUMÉROS DE COMMANDE

WLL kg Angle 0°	XOPSR-00-08N	XOPSR-00-10N	XOPSR-00-12N	XOPSR-01-16N	XOPSR-02-20N	XOPSR-03-24N	XOPSR-04-30N	XOPSR-07-36N	XOPSR-09-42N
600 kg	2016782	-	-	-	-	-	-	-	-
800 kg	-	2016783	-	-	-	-	-	-	-
1500 kg	-	-	2016784	-	-	-	-	-	-
3000 kg	-	-	-	2016785	-	-	-	-	-
4600 kg	-	-	-	-	2016786	-	-	-	-
6400 kg	-	-	-	-	-	2016787	-	-	-
9000 kg	-	-	-	-	-	-	2016788	-	-
14000 kg	-	-	-	-	-	-	-	2016789	-
18000 kg	-	-	-	-	-	-	-	-	2016790
24000 kg	-	-	-	-	-	-	-	-	-

■ Matériel principal

Acier

■ Couleur

Orange

■ Contenu des unités d'emballage (UE)

1

